Cationic Detergent for Load Process (Injection) **Use in Perchloroethylene**

TOP CATTM



TOP CAT is formulated to be the top performance cationic injection detergent for perc. As a properly formulated cationic substantive detergent, TOP CAT provides lubrication to fibers for a soft hand, prevents static and lubricates zippers - but will not build up or form gummy residue on fabric or in equipment.

• Superb cleaning power

- Effective stain removal
- Consistent cleaning performance
- A soft hand and drape
- Effective removal of "sweet spots" and control of static without adding additional water
- Superior lint control
- Excellent control over redeposition
- Brighter colors and whiter whites
- Elimination of sticky zippers
- Versatility: may be used in a one-bath or two-bath cleaning process





TOP CAT Use Instructions

For professional drycleaning use only. Before using any chemical product, review the Safety Data Sheet (SDS) for safe handling and proper disposal.

Load Process (Injection) Use

- Although not required, for best results, a 3-minute batch prewash is recommended to remove loose soil, grease, bleeding dyes, and stain removal additives. For heavy soil or potential dye bleed items, a 3-minute batch prewash is strongly recommended.
- After 1 minute of fill, and once garments are wet with solvent, inject **TOP CAT** either into the wheel, fill line, or button trap. NOTE: if detergent is injected into the button trap or fills through a filter, delay detergent injection until fill is finished and "milling"* starts-normally about 30 seconds.
- For soil and stain removal, inject **TOP CAT** at a rate of 2 oz. per 10 lbs. (130 mL per 10 kg) of garments.
- Run 5 minutes with circulating solvent, bypassing filter (milling*) to release soil.
- Fill wheel to high level from work tank and inject sizing if desired, circulate through filter system for 5 to 10 minutes (depended on amount of soil and flow rate in the machine) to remove released soil.

<u>NOTE</u>: Fragile garments should be run 3 minutes on batch (or milling*) then 3 minutes on filter to reduce mechanical action. Do not prewash. <u>NOTE</u>: Garments pre-treated with water-based spotters should be allowed to partially dry before cleaning.

* "Milling" means circulation from wheel through button trap and back to wheel (no filter).

How to Order TOP CAT

Order from your authorized Adco-Laidlaw local distributor in 5-gallon pails (18.93 L), and 15-gallon (56.78 L) and 55-gallon (208.19 L) drums.

800.821.7556 Adco Professional Products, LLC, Albany, GA 31707 © 2019. TOP CAT[™] is a Trademarks of Adco Professional Products, LLC. # A105-181002

