



# C-300™

Detergent, Brighteners, Softener, & Conditioners



## DRYCLEANING Combination Load Process (Injection) Detergent For Use in HC Boost™, LIFT™, High Flash Hydrocarbon, & Petroleum Solvents

**C-300** is an effective cationic injection detergent formulated in combination with optical brighteners, softeners, and conditioners that are designed to remain on cleaned garments. **C-300** is completely soluble in solvent so that it is picked up and absorbed evenly in the load – with no splotchy cleaning or plugged filters. **C-300** is Adco's premier cationic injection detergent for Ktex, hydrocarbon and other petroleum systems because it provides:

- Superior cleaning power and stain removal
- Excellent moisture control to help effectively remove water soluble soils without adding additional water
- Excellent control over redeposition
- Effective static control
- Brighter colors and whiter whites
- Elimination of sticky zippers
- A truly effective optical brightener system that competitive products do not match for uniformity and intensity
- Conditioners and softeners which provide lubricity to fibers for a soft hand, a like new shine and feel to garments – but will not build up on fabric or equipment

DRYCLEANING



+1 (630) 416-4244  
Adco Professional Products, LLC, Chicago, IL 60608



## C-300 Use Instructions

For professional drycleaning use only. Before using any chemical product, review the Safety Data Sheet (SDS) for safe handling and proper disposal.

### Load Process (Injection) Use

- **C-300** may be used in a one-bath or two-bath cleaning process.
- Although not required, for best results, a 3-minute batch prewash is recommended to remove loose soil, grease, and bleeding dyes and stain removal additives.
- After garments are wet with solvent, inject **C-300** either into wheel, fill line or button-trap while the solvent is circulating. Bypass the filter/with filter off.
- For optimum soil and stain removal, inject 2 oz. (60 mL) of **C-300** for each 10 lbs. (4.5 kg) of garments. For lightly soiled loads, use 1 oz. (30 mL) of **C-300** per 10 lbs. (4.5 kg) of garments.
- After introducing **C-300** into the wheel, the load must be run on batch or “milled,” circulated from wheel to button trap and back to wheel with the circulating solvent bypassing the filter for 5 minutes.
- After the batch or milling period, run on filter based on the following:
  - For light soil loads: 5 minutes on filter.
  - For regular loads without pre-rinse, depending on soiling: 5-15 Minutes.
  - For heavily soiled loads: at least 15 minutes.

**NOTE:** Fragile garments should be run 3 minutes on batch (or milling) then 5 minutes on filter to reduce mechanical action. Do not prewash.

**NOTE:** A 5-minute pre-rinse to the still is recommended for heavy soil or potential dye bleed items.

**NOTE:** **C-300** contains enough water to effectively remove water-soluble stains and control static without adding additional water. Addition of small amounts of supplementary water (by injection or prespotting) could improve results in dry climates. **C-300** will handle limited amounts of additional moisture when used at the 2 oz. (60 mL) per 10 lb. (4.5 kg) level.

### How to Order C-300

Order from your authorized Adco -Laidlaw local distributor in 5-gallon pails, 15-gallon drums

