



# PERK SHEEN 324<sup>®</sup>

## PREMIUM DETERGENT FOR PERCHLOROETHYLENE SYSTEMS

**Perk Sheen 324** is a powerful charge/injection detergent for use in perchloroethylene systems.

- Provides Superior Cleaning
- Effectively Controls Moisture
- Reduces Redeposition of Soil
- For Charge or Injection Systems
- Leaves a Soft, "Like New" Finish
- Helps Prevent Sticking Zippers



DETERGENT



1-630-416-4244

Adco Professional Products, LLC, Chicago, IL 60608



## Perk Sheen 324 Use Instructions

*For professional drycleaning use only. Before using any chemical product, review the Safety Data Sheet (SDS) for safe handling and proper disposal. When adding Perk Sheen 324 for the first time, to ensure the best results, start with new or distilled solvent in the working tank and filter system. Purge all old detergent from the addition pump and detergent feed lines.*

### For Use In Charged Solvent Systems:

For best results, a charge of 1% should be maintained.

### First Time Charge:

Add **Perk Sheen 324** at a rate of 13 oz. per 10 gallons (or 100 ml per 10 L) of solvent in work tank, piping, and filter plus 1/4 gallon (950 mL) for each large adsorption cartridge (if any).

### To Maintain Charge:

Add **Perk Sheen 324** at a rate of 1.25 ounces for each gallon (or 10 mL per 1 L) of new or recovered solvent added to to work tank or, if easier, add 12 ounces per 100 lbs. (or 80 mL for each 10 kg) of load cleaned.

### For Machines Equipped with Injectors:

Inject **Perk Sheen 324** at a rate of 1 to 2 oz per 10 lbs. (or 65-130 mL per 10 kg) of load at start of filter run to maintain charge.

### How to Order Perk Sheen 324

Perk Sheen 324 is sold by authorized Adco distributors. Order from your local distributor in single one-gallon (3.785 L) containers, boxes of four 1-gallon containers, 5-gallon pails or 5-gallon drums.