

SOFT KLEEN XTRA™

Drycleaning Detergent



Detergent for Charge or Load (Injection) Process Use in Perchloroethylene

SOFT KLEEN XTRA is an outstanding drycleaning detergent. The product's unique advanced formulation neutralizes electrical charge to not only control the static and lint, but also to provide a soft, luxurious, cling-free feel to fabrics.

- Provides superior cleaning power and stain removal
- Produces softer feeling and draping garments
- Helps prevent static, cling and linting
- Has excellent moisture control to help effectively remove water soluble soils
- Versitile: can be used in charge or load (injection) process systems
- Helps reduce and elminate redeposition
- Offers a truly effective optical brightener system for consistent uniformity and intensity of colors and whites





SOFT KLEEN XTRA Use Instructions

For professional drycleaning use only. Before using any chemical product, review the Safety Data Sheet (SDS) for safe handling and proper disposal.

In order to ensure the best results, start with new or distilled solvent in the working tank and filter system. Purge all of the old detergent from the addition pump and detergent feed lines. To ensure optimum performance it is necessary to condition the system with SOFT KLEEN XTRA. To calculate the amount of SOFT KLEEN XTRA required for conditioning, first total the number of gallons of solvent in the system. To arrive at the total, add the volume of solvent in the working tank to that estimated to be in the filter and piping. Conditioning of the solvent in the system should be done any time the majority of the solvent in the system is replaced with new or distilled solvent. After adding SOFT KLEEN XTRA, circulate the solvent through the washer, filter, piping and tank system by running a wash cycle without any garments in the wheel for 5 minutes. This ensures uniform distribution of SOFT KLEEN XTRA before starting the first load.

Charged Solvent Systems

Conditioning/First Time Charge

Condition system with **SOFT KLEEN XTRA** at a rate of 1 gallon per 100 gallons (or 100 ml per 10 L) of solvent in work tank and filter plus 1/4 gallon (950 mL) for each large adsorption cartridge (if any).

To Maintain Charge:

Add at a rate of 1.25 ounces for each gallon (or 10 mL per 1 L) of new or recovered solvent added to system or, if easier, add 10 ounces per 100 lbs (or 65 ml for each 10 kg) of load cleaned.

Load Process (Injection) Use

Conditioning/First Time

First initially condition system with **SOFT KLEEN XTRA** at a rate of 1 gallon for each 100 gallons (or 100 mL for each 10 L) of solvent in work tank and filter plus 1/4 gallons (950 mL) for each large adsorption cartridge (if any).

Load (Injection) Use

Use **SOFT KLEEN XTRA** at the start of the filter run at the following rates:

- If No pre-rinse is used: 1 oz. per 10 lbs. (or 65 mL per 10 kg).
- If pre-rinse uses distilled solvent: 1 oz. per 10 lbs. (or 65 mL per 10 kg).
- If pre-rinse uses solvent from work tank: 2 oz. per 10 lbs. (or 130 mL per 10 kg).

How to Order SOFT KLEEN XTRA

Order from your authorized Adco -Laidlaw local distributor in single one-gallon containers (3.785 L), cases of four, 5-gallon pails (18.93 L), 15-gallon drums (56.78 L), and 55-gallon (208.2 L) drums.



