



BoilSoft™

Boiler Water Treatment for Soft Water Fed Boilers



BoilSoft is a boiler treatment compound specifically formulated to be used in boilers fed by soft water. Soft water can cause problems to boilers when left untreated such as:

1. Increased solids leading to foaming and surging
2. Excess alkalinity which can result in stress cracking
3. Formation of hard scale on tubes

BoilSoft is specially formulated to help prevent these problems.

- Designed For Soft Water Conditions
- Helps Improve Boiler Efficiency
- Reduces Scale Build Up
- Helps Prevent Corrosion, Formation Of Scale, and Oxygen Pitting
- Helps Protects Steam and Condensate Lines
- Formulated To Be Non-Foaming



BoilSoft Use Instructions

For professional drycleaning & laundry boiler use only. Read Safety Data Sheet for further instructions, warnings, and first aid information before using this product.

Add **BoilSoft** to the make-up tank prior to blowing down the boiler. Add ½ oz. (15 mL) BoilSoft per boiler Horse Power (H.P). per day. For example, for a 15 H.P. boiler, use 8 oz. (240 mL). For best results, water samples from the boiler should be analyzed periodically to assure an adequate level of treatment is being used. Ask your Adco/Street's representative about our boiler water analysis service.

Note: Important – blow down boiler daily. Caution must be used whenever a water treatment is introduced into a boiler that has been in service for some time with no treatment, as there is a possibility that loosened scale and rust could cause system problems such as clogged steam traps and contamination of steam. In all cases, use **BoilSoft** in accordance with the product usage instructions and the boiler manufacturer's operating instructions and recommended preventative maintenance procedures.

How to Order BoilSoft

Order from your authorized Adco – Laidlaw local distributor in 1-gallon containers, boxes of four 1-gallon containers, 5-gallon pails, and 15-gallon drums.